



Technical Data Sheet

Chemmot Ewa & Jerzy Kumorek spółka jawna
PL 32-050 Skawina, ul. Piłsudskiego 59

Telefon: 12 276 75 45
Telefax: 12 276 78 20

DECO COLOR® znak towarowy CHEMMOT®
DECO COLOR® najlepiej postrzegany brand farb i lakierów w aerozolu

Trade name

CONTACT SPRAY by DECO COLOR® aerosol line

Article No

30 720

Seller/Manufacturer

Chemmot Ewa & Jerzy Kumorek spółka jawna; Piłsudskiego 59, 32-050 Skawina, Polska

Product's description

Moisture remover from electrical installations. Helps in ignition process. Eliminates oxidized places on contacts, causing uninterrupted electricity stream. Preserves electrical systems in vehicles. Prevents oxidation and sulfidation in pipes, electrical contacts, sockets, connectors, fuses and spark plugs.

Main features

Provides uninterrupted electricity stream in sockets
Protects against water, salt, and weak acids
Anticorrosive properties
Penetrating properties
Removes oxidized places
For indoor and outdoor use
CFC free

Physical and Chemical Properties

Capacity	400 ml
Colour	clear
Application temperature	10-25°C
VOC content	about 80%
Solids content	about 20%

Usage

Prepare the surface. Clean carefully, degrease, and be sure places you would like to apply to be dry.

Shake container vigorously for around 1 minute.

Apply selected places evenly from 30 cm. In case of inaccessibility of some places, please use actuator (pipe/tube).

Wait few minutes. Start engine. If any problems, spread to whole ignition system.

Wait few minutes.

If necessary wipe excess with a soft cloth.

Technical Data Sheet version 04 from 25/03/2014