



# Technical Data Sheet

Chemmot Ewa & Jerzy Kumorek spółka jawna  
PL 32-050 Skawina, ul. Piłsudskiego 59

Telefon: 12 276 75 45  
Telefax: 12 276 78 20

DECO COLOR® znak towarowy CHEMMOT®  
DECO COLOR® najlepiej postrzegany brand farb i lakierów w aerozolu

## Trade name

**SILICON SPRAY by DECO COLOR® aerosol line**

## Article No

30 710

## Seller/Manufacturer

Chemmot Ewa & Jerzy Kumorek spółka jawna; Piłsudskiego 59, 32-050 Skawina, Polska

## Product's description

Hydrophobic lubricant for preservation of rubber and plastic parts of the car, home and industry. Protects against water and oxidation. Protects rubber parts against drying and freezing. Preserves plastic and makes it more glossy. Refreshes mat paint coatings. Helps in mounting windows. Good grease for locks, hinges and chains. Helps to remove elements from their forms. Gives electrical insulation due to its ant static properties.

## Main features

Odourless, non-toxic, colourless  
Reduces friction, eliminates creaks and squeaks  
Resistant to temperatures from - 50°C to + 200°C  
Petrol resistance  
Weather condition resistance  
Good insulator  
Antistatic: does not attract dirt and dust  
For indoor and outdoor use  
CFC free

## Physical and Chemical Properties

Capacity	400 ml
Colour	clear
Gloss	high gloss / mat
Application temperature	15-25°C
High temperature resistance	from -50°C up to 200°C
VOC content	about 70%
Solids content	about 30%



# Technical Data Sheet

Chemmot Ewa & Jerzy Kumorek spółka jawna  
PL 32-050 Skawina, ul. Piłsudskiego 59

Telefon: 12 276 75 45  
Telefax: 12 276 78 20

DECO COLOR® znak towarowy CHEMMOT®  
DECO COLOR® najlepiej postrzegany brand farb i lakierów w aerozolu

## Usage

Prepare the surface; Clean carefully, degrease, and be sure places you would like to apply grease to be dry.

Shake container vigorously for around 1 minute.

Apply selected places evenly from 30 cm. In case of inaccessibility of some places, please use actuator (pipe/tube).

Wait few minutes.

If necessary wipe excess with a soft cloth.

Could be used to car's boot seals, doors, hood at winter periods as well as after each car washing.

Technical Data Sheet version 04 from 25/03/2014

